

Reference data

Eaton 5S 550AU



Product	Eaton Ref	Short description
Eaton 5S 550AU	5S550AU	Superior UPS, compact protection for Workstations, 550VA/330W, Line-Interactive with booster & fader, built-in surge protection, USB port, slim-line design, versatile form factor, Tel/Internet/Ethernet protection, 6 ANZ outlets (3 with battery backup and surge protection + 3 with surge protection only)

Packaging	Size (H x W x D*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	330 x 164 x 328	5,6 kg	1 product / carton	74317243627
Complete pallet	1120 x 1200 x 1000	373 kg	63 cartons / pallet	

Package content
UPS + USB Cable + 18-language User manual + Safety instructions + LPG warranty statement

Technical specifications	
Technology	Line-Interactive (AVR with Booster + Fader)
Power output	550 VA / 330 W
Size (H x W x D*)	250 x 87 x 260 mm
Weight	4,96 kg
Outlets	6 ANZ outlets (3 with battery back up and surge protection + 3 with surge protection)
Output voltage	240 V
Frequency	50 / 60 Hz auto-select
Input voltage range	175V-275V
Features	Automatic battery test, replaceable battery, resettable circuit breaker, audible alarm, permanent battery recharge (even when off), cold start
Data line protection	Tel/Internet/Ethernet protection
Power management	1 USB port, HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux)
Warranty	2 years ; optional PLP Warranty + (3, 4, 5 year options)
Technical standards	IEC 62040-1, IEC 62040-2, CE mark, CB Report, C-Tick

Runtime in Minutes	10%	30%	50%	70%
5S 550AU	65	18.5	9.5	5.5

Key selling points
<ul style="list-style-type: none"> • Ideal protection 550VA/330W for Workstations • Automatic Voltage Regulation (AVR) • Compact slim-line design : saves desk space, versatile installation : vertical or horizontal • 6 outlets : 3 with battery backup and surge protection + 3 with surge protection only • 1 USB port (cable supplied), HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux) • Tel/Fax/Modem/Internet/Ethernet protection • Replaceable battery • Audible alarm • Resettable circuit breaker

* H x W x D = Height x Width x Depth

Options	Reference
Warranty + (3 year-warranty)	WP812
Warranty + (4 year-warranty)	WP812-4
Warranty + (5 year-warranty)	WP812-5

Reference data

Eaton 5S 700AU



Product	Eaton Ref	Short description
Eaton 5S 700AU	5S700AU	Superior UPS, compact protection for Workstations, 700VA/420W, Line-Interactive with booster & fader, built-in surge protection, USB port, slim-line design, versatile form factor, Tel/Internet/Ethernet protection, 6 ANZ outlets (3 with battery backup and surge protection + 3 with surge protection only)

Packaging	Size (H x W x D*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	330 x 164 x 328	6,6 kg	1 product / carton	74317243634
Complete pallet	1120 x 1200 x 1000	436kg	63 cartons / pallet	

Package content
UPS + USB Cable + 18-language User manual + Safety instructions + LPG warranty statement

Technical specifications	
Technology	Line-Interactive (AVR with Booster + Fader)
Power output	700 VA / 420 W
Size (H x W x D*)	250 x 87 x 260 mm
Weight	5,98 kg
Outlets	6 ANZ outlets (3 with battery back-up and surge protection + 3 with surge protection)
Output voltage	240 V
Frequency	50 / 60 Hz auto-select
Input voltage range	175V-275V
Features	Automatic battery test, replaceable battery, resettable circuit breaker, audible alarm, permanent battery recharge (even when off), cold start
Data line protection	Tel/Internet/Ethernet protection
Power management	1 USB port, HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux)
Warranty	2 years ; optional PLP Warranty + (3, 4, 5 year options)
Technical standards	IEC 62040-1, IEC 62040-2, CE mark, CB Report, C-Tick

Runtime in Minutes	10%	30%	50%	70%
5S 700AU	62	18	8.5	5

Key selling points
<ul style="list-style-type: none"> • Ideal protection 700VA/420W for Workstations • Automatic Voltage Regulation (AVR) • Compact slim-line design : saves desk space, versatile installation : vertical or horizontal • 6 outlets : 3 with battery backup and surge protection + 3 with surge protection only • 1 USB port (cable supplied), HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux) • Tel/Fax/Modem/Internet/Ethernet protection • Replaceable battery • Audible alarm • Resettable circuit breaker

* H x W x D = Height x Width x Depth

Options	Reference
Warranty + (3 year-warranty)	WP812
Warranty + (4 year-warranty)	WP812-4
Warranty + (5 year-warranty)	WP812-5

Reference data

Eaton 5S 850AU



Product	Eaton Ref	Short description
Eaton 5S 850AU	5S850AU	Superior UPS, compact protection for Workstations, 850VA/510W, Line-Interactive with booster & fader, built-in surge protection, USB port, slim-line design, versatile form factor, Tel/Internet/Ethernet protection, 6 ANZ outlets (3 with battery backup and surge protection + 3 with surge protection only), Eco Control Function, LCD Interface.

Packaging	Size (H x W x D*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	330 x 164 x 328	7,4 kg	1 product / carton	74317243641
Complete pallet	1120 x 1200 x 1000	486 kg	42 cartons / pallet	

Package content
UPS + USB Cable + 18-language User manual + Safety instructions + LPG warranty statement

Technical specifications	
Technology	Line-Interactive (AVR with Booster + Fader)
Power output	850 VA / 510 W
Size (H x W x D*)	250 x 87 x 260 mm
Weight	6,5 kg
Outlets	6 ANZ outlets (3 with battery back-up and surge protection + 3 with surge protection), Eco Control function
Output voltage	240 V
Frequency	50 / 60 Hz auto-select
Input voltage range	175V-275V
Features	Automatic battery test, replaceable battery, resettable circuit breaker, audible alarm, permanent battery recharge (even when off), cold start
Data line protection	Tel/Internet/Ethernet protection
Power management	1 USB port, HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux)
Warranty	2 years ; optional PLP Warranty + (3, 4, 5 year options)
Technical standards	IEC 62040-1, IEC 62040-2, CE mark, CB Report, C-Tick

Runtime in Minutes	10%	30%	50%	70%
5S 850AU	62	19	8.5	5

Key selling points
<ul style="list-style-type: none"> • Ideal protection 1200VA/750W for Workstations • LCD Interface • Automatic Voltage Regulation (AVR) • Compact slim-line design : saves desk space, versatile installation : vertical or horizontal • 6 outlets : 3 with battery backup and surge protection + 3 with surge protection only • Energy saving Eco Control function • 1 USB port (cable supplied), HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux) • Tel/Fax/Modem/Internet/Ethernet protection • Replaceable battery • Audible alarm • Resettable circuit breaker

* H x W x D = Height x Width x Depth

Options	Reference
Warranty + (3 year-warranty)	WP812
Warranty + (4 year-warranty)	WP812-4
Warranty + (5 year-warranty)	WP812-5

Reference data

Eaton 5S 1200AU



Product	Eaton Ref	Short description
Eaton 5S 1200AU	5S1200AU	Superior UPS, compact protection for Workstations, 1200VA/750W, Line-Interactive with booster & fader, built-in surge protection, USB port, slim-line design, versatile form factor, Tel/Internet/Ethernet protection, 6 ANZ outlets (3 with battery backup and surge protection + 3 with surge protection only), Eco Control function, LCD interface

Packaging	Size (H x W x D*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	326 x 160 x 490	10,4 kg	1 product / carton	74317243658
Complete pallet	1113 x 1200 x 1000	457 kg	42 cartons / pallet	

Package content
UPS + USB Cable + 18-language User manual + Safety instructions + LPG warranty statement

Technical specifications	
Technology	Line-Interactive (AVR with Booster + Fader)
Power output	1200 VA / 750 W
Size (H x W x D*)	250 x 87 x 382 mm
Weight	9,48 kg
Outlets	6 ANZ outlets (3 with battery back-up and surge protection + 3 with surge protection), Eco Control function
Output voltage	240 V
Frequency	50 / 60 Hz auto-select
Input voltage range	175V-275V
Features	Automatic battery test, replaceable battery, resettable circuit breaker, audible alarm, permanent battery recharge (even when off), cold start
Data line protection	Tel/Internet/Ethernet protection
Power management	1 USB port, HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux)
Warranty	2 years ; optional PLP Warranty + (3, 4, 5 year options)
Technical standards	IEC 62040-1, IEC 62040-2, CE mark, CB Report, C-Tick

Runtime in Minutes	10%	30%	50%	70%
5S 1200AU	70	20	9	5

Key selling points
<ul style="list-style-type: none"> • Ideal protection 1200VA/750W for Workstations • LCD Interface • Automatic Voltage Regulation (AVR) • Compact slim-line design : saves desk space, versatile installation : vertical or horizontal • 6 outlets : 3 with battery backup and surge protection + 3 with surge protection only • Energy saving Eco Control function • 1 USB port (cable supplied), HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux) • Tel/Fax/Modem/Internet/Ethernet protection • Replaceable battery • Audible alarm • Resettable circuit breaker

* H x W x D = Height x Width x Depth

Options	Reference
Warranty + (3 year-warranty)	WP812
Warranty + (4 year-warranty)	WP812-4
Warranty + (5 year-warranty)	WP812-5

Reference data

Eaton 5S 1600AU



Product	Eaton Ref	Short description
Eaton 5S 1600AU	5S1600AU	Superior UPS, compact protection for Workstations, 1600VA/1000W, Line-Interactive with booster & fader, built-in surge protection, USB port, slim-line design, versatile form factor, Tel/Internet/Ethernet protection, 6 ANZ outlets (3 with battery backup and surge protection + 3 with surge protection only), Eco Control function, LCD interface

Packaging	Size (H x W x D*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	326 x 160 x 490	12,4 kg	1 product / carton	74317243665
Complete pallet	1113 x 1200 x 1000	541 kg	42 cartons / pallet	

Package content
UPS + USB Cable + 18-language User manual + Safety instructions + LPG warranty statement

Technical specifications	
Technology	Line-Interactive (AVR with Booster + Fader)
Power output	1600 VA / 1000 W
Size (H x W x D*)	250 x 87 x 382 mm
Weight	11,08 kg
Outlets	6 ANZ outlets (3 with battery back-up and surge protection + 3 with surge protection), Eco Control function
Output voltage	240 V
Frequency	50 / 60 Hz auto-select
Input voltage range	175V-275V
Features	Automatic battery test, replaceable battery, resettable circuit breaker, audible alarm, permanent battery recharge (even when off), cold start
Data line protection	Tel/Internet/Ethernet protection
Power management	1 USB port, HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux)
Warranty	2 years ; optional PLP Warranty + (3, 4, 5 year options)
Technical standards	IEC 62040-1, IEC 62040-2, CE mark, CB Report, C-Tick

Runtime in Minutes	10%	30%	50%	70%
5S 1600AU	68	19	9	5

Key selling points
<ul style="list-style-type: none"> • Ideal protection 1600VA/1000W for Workstations • LCD Interface • Automatic Voltage Regulation (AVR) • Compact slim-line design : saves desk space, versatile installation : vertical or horizontal • 6 outlets : 3 with battery backup and surge protection + 3 with surge protection only • Energy saving Eco Control function • 1 USB port (cable supplied), HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux) • Tel/Fax/Modem/Internet/Ethernet protection • Replaceable battery • Audible alarm • Resettable circuit breaker

* H x W x D = Height x Width x Depth

Options	Reference
Warranty + (3 year-warranty)	WP812
Warranty + (4 year-warranty)	WP812-4
Warranty + (5 year-warranty)	WP812-5